

Duct Inspection Camera

General information about Air Care Heat Exchanger Inspection Camera Scope Duct HVAC Inspection Tool AD-D2112REC

- ✓ For dia 25mm to 200mm(1"- 8") pipelines
- ✓ ø23mm stainless steel color camera head
- ✓ 12pcs adjustable LED
- ✓ Reel with 30m of 5mm dia Push Rod
- ✓ 8" LCD screen with sunshade, DVR supports voice recording, video recording, taking picture by any SD card (8GB SD card Included)
- ✓ Includes 2 skids: 40mm; 85mm



Technical specification of the device:

23mm camera head (removable):

- Total Pixels:PAL:710X576; NTSC:720X480
- Camera size:Ø23mmX(L)118mm
- View angle:120°
- Sensor size:1/4 CMOS 420TVL
- Camera shell material:stainless steel
- Camera glass material:sapphire glass

LED Lights(adjustable):

- LED Lights:12LEDS
- Brightness of the LEDS:Controllable

8inch screen:

- Size of the screen:8" LCD Monitor
- 4:3 model
- Total Pixels:800X600
- Monitor power supply:DC 12V
- OSD language:English
- Remote controller
- Sunshade include

Control box:

- Video format:AVI
- Picture format:MPEG2
- Memory card:8G(Maximum 64G)
- Audio, video, photo recording & playback function
- Digital clock and calendar
- Battery level indicator lights
- LED brightness adjustable
- On / off microphone
- Up, down, left, right adjustable
- Video output to another screen

Cable reel:

- Length:20m standard cable; 20-40m(optional)
- Diameter:5.2mm
- Reel size: L51xW25xH64cm



Centering skid:

- Dia 40mm/80mm:make the camera in the center of the pipe, and protect the camera head

Power supply:

- Li-ion Battery:DC12V 6600mah
- Working time:In operation(LED on): 6 hours

Case:

- Material:engineering plastics
- Color optional:orange/black
- The total weight includes all components:12KG-52X45X21cm

