

Inspection Camera Scope

General information about Air Care Heat Exchanger Inspection Camera Scope Duct HVAC Inspection Tool AD- P2012RE:

- ✓ Video Inspection Camera for Pipe, Duct, Sewer, Drain, Plumbing AD-P2012RE
- ✓ For dia 25mm to 200mm(1"- 8") pipelines
- ✓ ø23mm stainless steel color camera head
- ✓ 12pcs adjustable LED
- ✓ Reel with 30m of 5mm dia Push Rod
- ✓ 8" LCD screen with sunshade, DVR supports voice recording, video recording, taking picture by any SD card (8GB SD card Included)
- ✓ Includes 2 skids: 40mm; 85mm.



Technical specification of the device:

23mm camera head(removable):

- Total Pixels: PAL:710X576; NTSC:720X480
- Camera size: Ø23mmX(L)118mm
- View angle:120°
- Sensor size:1/4 CMOS 420TVL
- Camera shell material:stainless steel
- Camera glass material: sapphire glass
- Push pipe -sewer camera AD-P2012RE
- LED Lights: 12LEDS
- Brightness of the LEDES: Controllable

8inch screen:

- Size of the screen: 8" LCD Monitor
- Total Pixels:800X600
- Monitor power supply:DC 12V
- OSD language: English
- Remote controller
- Sunshade include

Control box:

- Video format:AVI
- Picture format: MPEG2
- Memory card: 8G(Maximum 64G)
- Audio, video, photo recording & playback function
- Digital clock and calendar
- Battery level indicator lights
- LED brightness adjustable
- On / off microphone
- Up, down, left, right adjustable
- Video output to another screen

Cable reel:

- Length: 20m standard cable; 20-40m(optional)
- Diameter: 5.2mm
- Reel size: L51xW25xH64cm



Centering skid:

- Dia 40mm/80mm: make the camera in the center of the pipe, and protect the camera head

Power supply:

- Li-ion Battery: DC12V 6600mah
- Working time: In operation(LED on): 6 hours

Case:

- Material: engineering plastics
- Color optional: orange/black
- The total weight includes all components :12KG, 52X45X21cm

