



duct inspection camera

General information about air duct push rod inspection camera video duct inspection camera AD-D2123RE

- ✓ For dia 25mm to 200mm(1"- 8") duct / HVAC
- ✓ ø23mm stainless steel color camera head
- ✓ 12pcs adjustable LED
- ✓ Reel with 30m of 5.2mm dia Push Rod
- ✓ 8" LCD screen with sunshade, DVR supports voice recording, video recording, taking picture by any SD card (8GB SD card Included)
- ✓ Includes 3 skids: 40mm; 85mm



Technical specification of the device:

23mm camera head(removable):

Total Pixels:PAL:710X576; NTSC:720X480
Camera size:Ø23mmX(L)118mm
View angle:120°
Sensor size:1/4 CMOS 420TVL
Camera shell material:stainless steel
Camera glass material:sapphire glass

LED Lights(adjustable):

LED Lights:12LEDS
Brightness of the LEDES:Controllable

8inch screen:

Size of the screen:8" LCD Monitor
4:3 model
Total Pixels:800X600
Monitor power supply:DC 12V
OSD language:English
Remote controller
Sunshade include

Control box:

Video format:AVI
Picture format:MPEG2
Memory card:8G(Maximum 64G)
Audio, video, photo recording & playback function
Digital clock and calendar
Battery level indicator lights
LED brightness adjustable
On / off microphone
Up, down, left, right adjustable
Video output to another screen

Cable reel:

Length:20m standard cable; 20-40m(optional)
Diameter:5.2mm
Reel size: L51xW25xH64cm



Centering skid:

Dia 40mm/80mm:make the camera in the center of the pipe, and protect the camera head

Power supply:

Li-ion Battery:DC12V 6600mah

Working time:In operation(LED on): 6 hours

Case:

Material:engineering plastics

Color optional:orange/black

The total weight includes all components:12KG-52X45X21cm

