

AC/DC hipot test

General information about VLF AC/DC hipot test AD-JS6A

AD-JS6A Automatic Insulation Test Set is special for insulated boots, gloves, blanket, mats, sleeves, clothes, hat, ladder, insulated baffle, chairs, insulated stick, electroscope and other security tools. It is automatic control.

Features:

- 320*240 LCD screen, high speed thermal printer.
- 8 measurement ways of HV voltage, LV current, 6-way leakage current.
- Automatic and manual operation for option.
- Real-time display the results, direct and clear.
- With over-voltage, over-current protection.
- With zero start function. The test can be proceed after returning to zero.
- Anti-interference design, suitable for harsh electromagnetic environment.
- Automatic error diagnosis, easy to find and solve problems.



Technical specification of the device:

Model No.	Rated Capacity	Input Voltage	Output Voltage	Voltage Accuracy	LV Current	Leakage Current	Resolution of leakage current	Current Accuracy
ADJS-63A	3kVA	220V	0-30kV	≤2.0%(F.S)	0-15A	0-20.0mA	0.1mA	≤1.5%(F.S)
ADJS-65A	5kVA	220V	0-50kV	≤2.0%(F.S)	0-25A	0-20.0mA	0.1mA	≤1.5%(F.S)
ADJS-610A	10kVA	220V	0-100kV	≤2.0%(F.S)	0-50A	0-20.0mA	0.1mA	≤1.5%(F.S)
ADJS-615A	15kVA	380V	0-150kV	≤2.0%(F.S)	0-37.5A	0-20.0mA	0.1mA	≤1.5%(F.S)

