

Sewer Inspection camera

General information about Video Sewer Inspection Push Rod Camera System, 60m Cable, Counter, Keyboard AD-P2013KC

- ✓ Video Sewer Inspection Push Rod Camera System, 60m Cable, Counter, Keyboard AD-P2013KC
- ✓ For dia 0mm to 400mm(6" - 16") pipelines
- ✓ Ø50mm Stainless steel color camera head
- ✓ 30pcs adjustable LED
- ✓ Reel with 120m of 9.5mm dia Push Rod
- ✓ 7" LCD screen with sunshade, DVR supports voice recording, video recording, taking picture by any SD card (8GB SD card Included)
- ✓ Meter/foot counting, text writing
- ✓ Includes 3 skids: 110mm; 150mm;220mm
- ✓ Ø50mm Stainless steel color camera head
- ✓ 12pcs adjustable LED
- ✓ Reel with 60m/120m of 9.5mm dia Push Rod
- ✓ 8" LCD screen with sunshade, DVR supports voice recording, video recording, taking picture by any SD card (8GB SD card Included)
- ✓ Meter/foot counting, text writing
- ✓ Includes 3 skids: 121mm; 141mm;213mm



Technical specification of the device:

50mm camera head(removable):

- Total Pixels: PAL:710X576; NTSC:720X480
- Camera size: Ø50mmX(L)100mm
- View angle:120°
- Sensor size: 1/3 CCD 700TVL
- Camera shell material: stainless steel
- Camera glass material:sapphire glass

LED Lights(adjustable):

- LED Lights:12LEDS
- Brightness of the LEDS: Controllable

8inch screen:

- Size of the screen:8" LCD Monitor
- 4:3 model
- Total Pixels: 800X600

Control box:

- Video format: AVI
- Picture format: MPEG2
- Memory card: 8G(Maximum 64G)
- A/V & photo selection available
- LED brightness adjusting knob

Cable reel:

- Length:60m standard cable; 60-120m(optional)
- Diameter:9mm
- Distance counter:Meter/foot
- Reel size: L84xW44xH93cm

Centering skid

- Dia 121mm/141mm/213mm: make the camera in the center of the pipe, and protect the camera head

Power supply:

- Li-ion Battery :DC12V 6600mah
- Working time:In operation(LED on): 6 hours

Case:

- Material:engineering plastics
- Color optional: orange/black
- The total weight includes all components: 45KG - 85X45X93cm (52X45X21cm)

