

Hydrogen sulfide Gas Detector

General information about ADGD-6010HS Hydrogen sulfide Gas Detector

Application:

- ✓ Furniture, flooring, wallpaper, paint, gardening, interior decoration and renovation, dyes, paper, pharmaceutical, medical, food, corrosion
- ✓ Disinfection, chemical fertilizers, resins, adhesives and pesticides, raw materials, samples, process and breeding plants, waste treatment plants, perm places
- ✓ Biopharmaceutical production workshops, home environment, livestock breeding, greenhouse cultivation, storage and logistics, brewing fermentation, agricultural production



Function

- Monitoring of the environment, or the concentration of formaldehyde in a confined space and give an alarm
- With self-check function, zero calibration function, so that gas monitoring more accurate and reliable
- One key to restore the factory settings, can be removed from misuse problems
- With temperature and pressure compensation, to achieve the perfect, different temperature and pressure environment, the gas concentration compensation
- Two sound and light alarm, alarm point can be set their own
- Large-capacity lithium polymer rechargeable battery
- Pump suction sampling, adjustable suction pump
- Shell with high-strength special engineering plastics, non-slip, waterproof, dustproof, explosion
- Exquisite upscale aluminum suitcase.

Feature

- Using imported high-precision electrochemical principles sensor
- USB interface high speed data transmission, can be downloaded print data (optional)
- LCD dot matrix display technology, can display the type of gas, the gas unit, gas concentration values, measured maximum, local time, ambient temperature, etc.
- Support Chinese and English operation interface, easy to switch
- Gas concentration unit PPM, mg/m³ can quickly switch display
- Built-in micro sampling pump, the pump suction size ten stalls adjustable
- Explosion-proof certification, proof grade: Exiall CT4



Technical Specification of the device:

- Gas Detected:Hydrogen sulfide (H₂S)
- Detection principle:Electrochemical principles
- Sampling Method:Pump- suction, flow up 1L/min, pump suction size ten stalls
- Adjustable
- Measure Range:0-10ppm, 0-50ppm, 0-100ppm, 0-500ppm, 0-1000ppm, 0-2000ppm,0-5000ppm, 0-10000ppm (option)
- Resolution:0.001ppm (0-10ppm), 0.01ppm (0-50ppm,0-100ppm), 0.1ppm (0-500ppm),1ppm (0-1000ppm)
- Precision:1% FS
- Signal Output:USB interface high speed data transmission, can be downloaded print data (optional)
- Response Time:≤ 10S
- Repeatability:≤ ± 1%
- Zero shift:≤ ± 1% (F.S / Year)
- Operating language:Support in English
- Temperature:-40 °C ~ 70 °C
- Explosion-Proof:Exia II CT4
- Alarm mode;Sound, light, vibration
- Dimensions:205*75*32mm
- Recovery Time:≤ 10S
- Linearity error:≤ ± 1%
- Display:LCD dot matrix display technology
- Gas unit:Support for multiple gas unit switch display
- Humidity:0-95% RH
- Degree of protection:IP66
- Operating time: hours (off pump)
- Weight(net/gross):300g/800g

