

Pneumatic comparator

General information about ADPC-7007 Pneumatic comparator:

- ✓ Pneumatic Pressure Comparison Pump is portable structure and designed to generate pressure from vacuum to 60bar.
- ✓ Built-in filter protects the pump from dirty and make maintenance easy and convenient.
- ✓ The F-adjust valve could accomplish 10Pa (0.1mbar) pressure resolution.
- ✓ Especially the lever lead screw design makes user operate in economize labor.
- ✓ the design of reverse valve makes the switch of vacuum and positive pressure more smooth.
- ✓ Two standard pressure outputs are easy to connect gauges under test without using the wrenches.
- ✓ It widely calibrates pressure instruments in field and laboratory.



Function:

ADPC-7007 provides pressure measurement for calibrating pressure instruments in field and laboratory.

It can be extensively used in power, chemical, petrol, metallurgy, metering, military industry, etc.

Characteristics:

portable structure

Built-in filter protects the pump from dirty and make maintenance easy and convenient

user operate in economize labor

Technical Specification of the device:

- Generated pressure range: (-0.95~16/25)bar The model HS702/(-0.95~40/60)bar The model HS703
- Working media: Air
- Adjust resolution: 0.1mbar
- Material: Body: Stainless steel /Aluminium/Seals:Buna-N
- Output interface connection: M20×1.5Female
- Weight:2.7kg
- Dimensions:286L×198W×140H (mm)

