

Pneumatic comparator

General information about ADPC-7009 Pneumatic comparator:

- ✓ Pneumatic Pressure Comparison Pump is designed with a reverse valve, generated pressure from vacuum to 60bar.
- ✓ The F-adjust valve could accomplish 10Pa (0.1mbar) pressure resolution.
- ✓ Having 3 outputs with fast fittings, which is more effective to calibrate 2pcs under test pressure instruments together.
- ✓ A built-in gas-oil isolator keeps the pump from oil impurity avoid some unnecessary maintenance.
- ✓ Especially the lever lead screw design makes user operate in economize labor.
- ✓ It widely calibrates pressure instruments in the laboratory.



Function:

ADPC-7009 provides pressure measurement for calibrating pressure (differential pressure) transmitter, precision pressure gauge, general pressure gauge and other pressure instruments.

It can be extensively used in power, chemical, petrol, metallurgy, metering, military industry, etc.

Characteristics:

- Food grade stainless steel and hermetic technology in the military industry
- High precision, stable pressure generating, easy operation.
- Wide pressurized range, high vacuum degree
- High reliability, Wide micro-adjusting range

Technical Specification of the device:

- Generated pressure range: (-0.95~60)bar
- Working media: Air
- Adjust resolution: 10Pa(0.1mbar)
- Material : Body:Stainless Steel/Aluminium/Seals:Buna-N
- Output interface connection: M20×1.5Female
- Weight:14.8kg
- Dimensions:380L×380W×200H (mm)

