

## Gaz Leak Detector

### General information about ADSF-GLD SF6 Gaz Leak Detector

ADSF-GLD SF6 Gas Leak Detector is infrared type leak detector. It is color LCD display and real-time shows SF6 concentration. It rapidly detects SF6 breaker, GIS leakage point and yearly leakage rate qualitatively and quantitatively. It's a good device suitable for power supply department, installation and overhaul unit, power test institute.

#### Features:

- ✓ LCD display
- ✓ User-defined alarm with sound and light
- ✓ High sensitivity and good stability
- ✓ Small size, easy to carry
- ✓ AC/DC on-site use

#### Technical Specification of the device:

- Measurement range: 0-300ppm SF6
- Sensitivity:  $\pm 0.1 \mu\text{L/L}$
- Resolution:  $0.1 \mu\text{L/L}$
- Storage temperature:  $-40 \sim +70^\circ\text{C}$
- Operation temperature:  $-10 \sim +60^\circ\text{C}$
- Sampling mode: Built-in electromagnetic diaphragm pump, automatic slot-in type.
- Working voltage: 220VAC $\pm 10\%$ , 50Hz Or Built-in Li-battery.
- Dimension: 200 $\times$ 270 $\times$ 140mm
- Weight: about 3kg.

